

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 August 2001 (23.08.2001)

PCT

(10) International Publication Number
WO 01/61625 A2

- (51) International Patent Classification⁷: **G06K 9/00** (74) Agent: **ERICSSON MOBILE COMMUNICATIONS AB**; IPR Department, S-221 83 Lund (SE).
- (21) International Application Number: **PCT/EP01/01397**
- (22) International Filing Date: 9 February 2001 (09.02.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
- | | | |
|------------|-------------------------------|----|
| 60/182,742 | 16 February 2000 (16.02.2000) | US |
| 60/190,343 | 16 March 2000 (16.03.2000) | US |
| 60/192,662 | 28 March 2000 (28.03.2000) | US |
| 60/244,775 | 31 October 2000 (31.10.2000) | US |
| 09/772,683 | 30 January 2001 (30.01.2001) | US |
- (71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET LM ERICSSON (publ)** [SE/SE]; S-126 25 Stockholm (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **HOLLSTRÖM, Magnus** [SE/SE]; Filippavägen 6A, S-222 41 Lund (SE). **GÄRDENFORS, Torbjörn** [SE/SE]; Kornettsgatan 24A, S-211 50 Malmö (SE). **JÖNSSON, Torsten** [SE/SE]; Kornvägen 19, S-245 43 Staffanstorps (SE).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
- without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 01/61625 A2

(54) Title: **ELECTRONIC PEN FOR E-COMMERCE IMPLEMENTATIONS**

(57) Abstract: A method and apparatus for performing electronic commerce transactions uses an electronic reading device having a sensor that detects portions of an address pattern. An electronic commerce client communicates with a remote electronic commerce server to perform an electronic commerce transaction in accordance with portions of the address pattern detected by the sensor. For example, the detected portions of the address pattern can be converted by the electronic commerce client into electronic commerce transaction data and sent to the electronic commerce server.

ELECTRONIC PEN FOR E-COMMERCE IMPLEMENTATIONS

BACKGROUND OF THE INVENTION

Technical Field of the Invention

5 The present invention relates in general to the communications field, and in particular to an interaction of an electronic reading device with an address pattern.

Description of Related Art

10 Numerous devices exist for accepting user input and controlling user interaction with desktop and portable computers, personal digital assistance (PDAs), mobile phones, and other types of electronic devices. For example, a keyboard can be used to accept typed input and other types of commands, a mouse or a track-ball can be used to provide relative motion input as well
15 as various types of point-and-click selections, a keypad can be used to provide input of numerical data and functional commands, navigational keys can be used for scrolling lists or otherwise repositioning a cursor, and various types of touchpads or touchscreens can be used to provide absolute positional coordinate
20 inputs. Each type of mechanism for accepting input and for supporting user interaction has benefits and disadvantages in terms of size, convenience, flexibility, responsiveness, and easy of use. Generally, the selection of a particular type of input mechanism is dependent upon the function of the application and
25 the degree and type of interaction required.

 With the ever expanding capabilities and availability of applications both on the Internet and the area of wireless technology, there continues to be a need to develop and provide new mechanisms for accepting input and interacting with users.
30 In particular, some of the existing technologies suffer from

drawbacks or limitations, such as size and flexibility, that make them impractical and/or inconvenient to use in some situations. By expanding the range of mechanisms for supporting user interaction, application developers and end-users can have greater flexibility in the selection of input devices. Preferably, any such new mechanisms will provide increased flexibility and will maximize user convenience. In addition, the development of new mechanisms for interacting with users can expand the realm of potential applications.

For example, while a keyboard typically provides a great deal of flexibility, particularly when it is used in connection with a mouse, a touchscreen, or other navigational device, its size makes it inconvenient in many cases, especially in the wireless context.

Furthermore, electronic commerce is expected to be an area of growth in the next few years. Today there exists means to perform electronic commerce over the Internet using a personal computer, and the telecom industry is developing solutions to do the same via mobile terminals (phones). Development of additional electronic commerce tools could provide even greater flexibility and convenience.

SUMMARY OF THE INVENTION

The present invention comprises a method, system, and apparatus for performing electronic commerce transactions. In accordance with the invention, a sensor in an electronic reading device detects portions of an address pattern. An electronic commerce client located in the electronic reading device or otherwise in communication with the electronic reading device converts the detected portions of the address pattern into electronic commerce transaction data. The electronic commerce

transaction data is then sent to an electronic commerce server for completing the electronic commerce transaction.

BRIEF DESCRIPTION OF THE DRAWINGS

5 For a more complete understanding of the present invention, reference is made to the following detailed description taken in conjunction with the accompanying drawings wherein:

FIGURE 1 is a block diagram of a system in which an electronic pen can be used as an input device;

10 FIGURE 2 is a schematic diagram of a system for supporting use of the electronic pen described in connection with FIGURE 1;

FIGURE 3 is an illustration of the protocol stacks that can be used in the case of local communications between an electronic pen and an electronic pen client;

15 FIGURE 4 is an illustration of protocol stacks that can be used when an electronic pen and an electronic pen client communicate with one another via an Internet connection;

20 FIGURE 5 is an illustration of a protocol stack for communications between an electronic pen client and each of the supporting entities when the electronic pen client is not located within a server on the Internet;

FIGURE 6 is an illustration of protocol stacks that are used for communications between an electronic pen client and each of the supporting entities when the electronic pen client is located on the Internet;

25 FIGURE 7 is a block diagram of the electronic pen logic that handles positions, strokes, actions, and grid descriptions;

FIGURE 8 is a block diagram of a state machine for the electronic pen control block shown in FIGURE 7;

30 FIGURE 9 is a block diagram of a state machine for an electronic pen client;

FIGURES 10A-10C are a message flow and signaling diagram illustrating the operation of the electronic pen system shown and discussed in connection with FIGURE 2; and

DETAILED DESCRIPTION OF THE INVENTION

5 The present invention relates to a system in which an electronic reading device, such as an electronic pen, an electronic mouse, or a hand scanner, works in cooperation with an address pattern (e.g., a specially formatted paper) to provide for a detection of a location of the electronic reading device over
10 the address pattern. For instance, a pattern of dots can be defined such that, by examining a very small portion of the pattern, a precise location in the overall pattern can be determined. In fact, it is possible to define a pattern that has the size of 73,000,000,000,000 A4 pages, which is equivalent to
15 half the size of the entire United States. Portions of the pattern can be placed on sheets of paper or other objects.

 Then, using an electronic scanner pen that can detect the dots in the pattern, it is possible to detect the location of the pen with respect to the unique pattern. For example, when such
20 a pen is used in connection with a specially formatted paper, the pen can detect its position (e.g., using a built in camera) by detecting a 3 mm by 3 mm portion of the pattern. By taking approximately 100 pictures per second, the pen is capable of determining its exact position to within 0.1 mm or less. This
25 system can be used to provide user input, to facilitate user interaction, or to store handwritten notes or drawings. Moreover, by associating portions of the overall pattern with certain applications, such a system can be used to interact with wide variety of applications.

Referring now to FIGURE 1, there is illustrated an example of a system 2 in which an electronic pen 10 can be used as an input device. The electronic pen 10 includes an ink cartridge and is capable of writing in a typical fashion. The electronic pen 10, however, includes some type of sensor (e.g., a built-in camera) that is used for detecting an address pattern on a specially formatted piece of paper 12. In particular, the paper 12 is formatted with a small portion of a large address pattern such that when the electronic pen 10 is used to write on or otherwise make marks on the paper 12, the writings or markings can be electronically detected and stored.

As an example, the paper 12 might constitute a form that can be used for sending an email. Thus, the paper 12 might include a space for writing in the email address of an intended recipient, a space for writing a subject of the email, and a space for writing the body of the email. As the electronic pen 10 is used to fill in each of the spaces, the position and movement of the electronic pen 10 on the paper 12 can be determined by repeatedly detecting the current x, y coordinates of the pen 10 (e.g., at rate of 100 frames per second). The markings can then be converted into ASCII text using an appropriate handwriting recognition program. Once the user completes the form, the email can be sent, for example, by checking a send box at a predetermined location on the paper 12.

Preferably, the coordinate information collected by the pen 10 is sent by a short range radio transmitter in the electronic pen 10 to a nearby mobile station 14 using a short range radio interface 16 such as a local wireless radio link (e.g., a local wireless radio link, such as that is supported by Ericsson's Bluetooth™ wireless communications technology). Alternatively,

instead of using a mobile station 14, the coordinate information could also be sent to, for instance, a desktop or portable computer, a personal digital assistant (PDA), a television, or a Bluetooth terminal. Moreover, instead of using a local wireless radio link, other types of local wireless links, such as inductive coupling and infrared light; other types of radio links, such as Global System for Mobile Communication (GSM); or wired transmission media, such as a cable can also be used. The information can then be forwarded via an appropriate link, such as a cellular air interface 18, to a base station 20 or other network node.

Referring now to FIGURE 2, there is illustrated a schematic diagram of a system 2 for supporting use of the electronic pen 10 described in connection with FIGURE 1. Throughout the subsequent discussion, the system 2 is described primarily in connection with an electronic pen 10. It will be understood, however, that the invention and the underlying system 2 can instead use any type of electronic reading device, such as an electronic pen, an electronic mouse, or a hand scanner. As shown in FIGURE 2, the system 2 includes six different entities, including the electronic pen 10, electronic pen client 22, a control node 24, a name server 26, a base translator 28, and an application server 30. Although these various devices are described and depicted separately, it is also possible to combine two or more of the entities into the same device (e.g., the electronic pen 10 and electronic pen client 22 can be contained in the same device).

The electronic pen 10 is responsible for detecting positions on the address pattern, producing actions, and sending information to the electronic pen client 22. In addition to being able to leave pen markings, some electronic pens can also have the ability

to produce other types of output, such as sound, vibration, or flashing lights. The electronic pen 10 includes a memory for storing a current grid, which comprises information relating to an area of the address pattern that is near the most recently
5 detected position of the electronic pen 10. When the electronic pen 10 is loaded with the current grid, it knows what actions to take based on the positions that are read from the address pattern. When the electronic pen 10 is first turned on or when it moves to an area outside of the current grid, the electronic
10 pen 10 must first request a new grid description before it can continue processing information. In such a situation, the electronic pen 10 requests a new grid description from the electronic pen client 22.

The electronic pen client 22 can be located in a mobile
15 station 14, in a PDA, in a desktop or portable computer, in the electronic pen 10 itself, in a server somewhere on the Internet, or in another device. The electronic pen client 22 serves as the center of communications in the overall system 2. In particular, the electronic pen client 22 receives new grid requests and action
20 requests from the electronic pen 10 and responds to these requests by contacting an appropriate entity within the overall system 2 to properly respond to the request from the electronic pen 10. Furthermore, when the electronic pen 10 is being used in connection with a particular application, the electronic pen
25 client 22 can store the application and/or any corresponding data received from the electronic pen 10 to facilitate processing and use of the application.

The name server 26 is used for translating a detected
position on the address pattern into a Uniform Resource Location
30 (URL) associated with that position. Different portions of the

address pattern are assigned to different applications. Neither the electronic pen 10 nor the electronic pen client 22, however, is aware of all of the different applications and the particular areas assigned to each application. Thus, when the electronic pen 5 10 detects a new or unknown position, it forwards the position information to the electronic pen client 22, which in turn sends the information to the name server 26. The name server 26 then identifies an application associated with the received position and retrieves a URL where a description of the particular 10 application can be found. The retrieved URL can then be used by the electronic pen client 22 to retrieve the application description.

As an alternative, the name server 26 can comprise a global name server that keeps track of a location, in the form of URLs 15 to local name servers, where more information can be found about different addresses in the pattern. Similarly, each local name server can use other local name servers to obtain the necessary information, i.e., to convert a position into a URL where an application description can be found. At the lowest level, the 20 local electronic pen client should know all the paper addresses that are within a specific application or applications.

There are some services that should be available in the overall system 2 for which it is inconvenient or not feasible to support such services in the electronic pen 10 or the electronic 25 pen client 22. In such a case, the base translator 28 can be used to support the services. For example, the base translator 28 might contain handwriting recognition software for converting pen actions into text or for converting pen actions into a predefined set of symbols. When such services are needed, the electronic pen 30 client 22 can send a request to the base translator 28 along with

the necessary data, and the base translator 28 can perform the requested service.

Another entity in the system 2 is a control node 24. The control node 24 is used for responding to actions in a standardized way. For example, the control node 24 can be used to respond to certain generic functions, such as "cancel" or "submit" functions, in a consistent manner without regard to the particular application that is currently active.

In addition, the control node 24 is used for creating streaming-like applications. For instance, some applications might require that the positions on the address pattern that are detected by the electronic pen 10 be immediately sent, upon detection, to the electronic pen client 22 for use by the application (i.e., the electronic pen 10 does not wait to transmit the position data until a complete stroke is detected or until a "send" field is touched). One example is an application that is used to control an industrial robot in a warehouse. In such a case, the application description that is loaded onto the electronic pen server 22 can include instructions that all positions be streamed to a control node 24. As a result, the control node 24 can receive the positions in real time and can control the robot without waiting for the form (i.e., the current grid) to be completed. Thus, the control node 24 can perform a real-time translation from detected positions to a responsive action, such as moving an object (e.g., a robot, a valve, etc.) or controlling a process.

The application server 30 is a regular web or wireless application protocol (WAP) server that supports an application associated with a particular area of the address pattern. The application server 30 stores an application description and

provides the application description to the electronic pen client 22 upon request. In addition, the application server 30 receives input data from the electronic pen 10 via the electronic pen client 22. For example, the application description might define a number of data entry areas on a form. Thus when data is entered on the form by the electronic pen 10, the data is received by the electronic pen client 22, converted into text using handwriting recognition software, and forwarded to the application server 30, which stores the data or otherwise processes the data in accordance with the function of the application.

Referring now to FIGURES 3 through 6 there are illustrated various examples of protocol stacks that can be used for communicating between the entities shown in FIGURE 2. Generally, however, such protocols apply however, only if the two communicating entities are implemented in different devices. If two or more entities are combined into one device, a proprietary protocol can be used to communicate between the entities. FIGURE 3 illustrates the protocol stacks that can be used in the case of local communications (e.g., using Bluetooth) between the electronic pen 10 and the electronic pen client 22. If, on the other hand, the electronic pen 10 and the electronic pen client 22 communicate with one another via an Internet connection, the protocol stacks depicted in FIGURE 4 will be used. FIGURE 5 illustrates a protocol stack for communicating between the electronic pen client and each of the supporting entities, such as the name server 26, the control node 24, the base translator 28, and the application server 30, when the electronic pen client 22 is not contained within a server on the Internet (e.g., such as when the electronic pen client 22 is located in a mobile phone

14). Finally, FIGURE 6 depicts the protocol stacks that are used when the electronic pen client 22 is located on the Internet.

There are a number of procedures that can be used by the various entities in the system 2 to allow the system to operate properly. When the electronic pen 10 detects a position on the address pattern that is not within its currently loaded grid or when the electronic pen 10 has no currently loaded grid, the electronic pen 10 initiates a new grid procedure. The new grid procedure involves sending a new grid request object to the electronic pen client 22. The new grid request object contains the newly detected position, a description of the actions that the electronic pen 10 can natively support, and a description of the output signals that the electronic pen 10 supports. The reply to a new grid request object is a grid description, which can be provided by the electronic pen client 22 from its own internal memory or from the information provided by an application server 30. Generally, the electronic pen client 22 extracts the grid description from an application description received from the application server 30. The grid description should only contain action-field-types that the electronic pen 10 has indicated that it natively supports, which means that the electronic pen client 22 in some cases should convert the extracted grid description into a format that the electronic pen 10 can understand.

In some situations, it may be necessary for the electronic pen 10 to unload its current grid at the request of the electronic pen client 22. In such a case, the electronic pen client 22 sends an empty grid description to the electronic pen 10, thereby causing the electronic pen 10 to unload its current grid. This can occur, for example, when a particular application is complete or when a new grid description request received from the

electronic pen 10 cannot be fulfilled, such as when the position received from the electronic pen 10 is not registered in the name server 26.

5 Another similar message is the empty grid description with a grid exception. When the electronic pen 10 requests a new grid description from the electronic pen client 22, the electronic pen client 22 uses the detected position specified in the request to ask the name server 26 for a URL where the application description can be found. If no URL is returned, the electronic pen client 10 22 can send an empty grid description with a grid exception to the electronic pen 10. The grid exception comprises a rectangle or other shape indicating the area around the detected position where no registered applications can be found. Preferably, the indicated area is as large as possible so that the electronic pen 15 10 and/or electronic pen client 22 know the extent of the surrounding area that is unassigned and do not have to repeatedly send requests to the name server 26. Thus, the empty grid description with a grid exception causes the electronic pen 10 to unload its current grid and also informs the electronic pen 10 of 20 an area surrounding the detected position that can essentially be ignored because its is not associated with any application.

The procedure that is used when the electronic pen 10 detects a new position is a find application description location procedure. This procedure is used by the electronic pen client 25 22 to translate a detected position received from the electronic pen 10 into a URL where a description of an application corresponding to that position can be found. The procedure involves sending a request from the electronic pen client 22 to the name server 26 containing identification of the detected 30 position. The name server 26 responds by sending a reply to the

electronic pen client 22 containing a URL where an application description can be found or, if the detected position is not registered in the name server 26, containing an indication that no associated application is known to exist.

5 Once the electronic pen client 22 knows the URL where an application description can be found, the electronic pen client 22 can initiate a get application description procedure, which allows the electronic pen client 22 to retrieve the application description from the application server 30. In particular, the
10 electronic pen client 22 sends an application description request containing a unique ID for the requesting electronic pen 10 and/or electronic pen client 22 to the application server 30 located at the URL address provided by the name server 26. In response, the application server 30 provides an application description object
15 to the electronic pen client 22, which loads the application onto the electronic pen client 22. The application description object is similar to an HTML form with some additions and modifications.

 Furthermore, the application description object can be sent from the application server 30 to the electronic pen client 22 in
20 response to a submitted form (i.e., a submission of one completed form might automatically result in a new form being loaded onto the electronic pen client 22). A related procedure is the application submit procedure, which is used by the electronic pen client 22 when the user of the electronic pen 10 selects a
25 "submit" field in a form. In response to the selection of the "submit" field, the electronic pen client 22 will submit the form content in accordance with instructions received in the application description. Typically, the electronic pen client 22 will submit the form content, in the same way as a regular web

browser, to a URL specified in a form tag of the application description.

When an action that can be handled by the electronic pen 10 itself is generated, an action procedure is initiated by the electronic pen 10 to send an action request object to the electronic pen client 22. If the electronic pen client 22 cannot translate the action into a field value itself, the electronic pen client 22 further forwards the request to a base translator 28 for translating the action into a field value. In response to the action request object, an action reply object is sent from the electronic pen client 22 to the electronic pen 10. The action reply object contains output information that indicates to the electronic pen 10 which outputs signals to use. The output information, however, cannot be of type that the electronic pen 10 has previously indicated that it does not support. In some instances, the action reply object might contain a new grid description. In such a case the electronic pen 10 will unload its current grid description and load the new grid description. Similarly, if the action reply object contains an empty grid description, the electronic pen 10 will simply unload its current grid description.

The action request object is also sometimes used to specify actions that should be processed by the control node 24. In this instance, the electronic pen client 22 initiates a control procedure by forwarding the received action to the appropriate control node 24. As a result, the control node 24 sends an action reply object to the electronic pen client 22.

The operation of the electronic pen 10 will now be discussed in greater detail. Each electronic pen 10 has a unique pen ID, which is sent to the application server 30 when an application

description is requested. The electronic pen ID allows the application to identify the particular user that is using the application and to distinguish between multiple concurrent users of the same application, such as when different electronic pens
5 10 are being used in connection with separate sheets of paper that each contain the same portion of the address pattern.

Referring now to FIGURE 7, there is illustrated a block diagram of the electronic pen logic that handles positions, strokes, actions, and grid descriptions for the electronic pen 10.
10 The electronic pen 10 includes a control block 32 for controlling the operation of the electronic pen 10. A grid description block 34 represents a memory location that stores a current grid description. At any given time, the electronic pen 10 can be in either of two modes. In a first mode, a grid description is
15 loaded, while in a second mode, the grid description block 34 is not loaded with a current grid description.

As the electronic pen 10 moves across an address pattern, the electronic pen 10 periodically (e.g., every 1/100 of a second) detects a position by detecting all of the dots within, for
20 example, a 3mm by 3mm area. Each detected position is forwarded (as indicated at 36) to a position first in first out (FIFO) block 38, which acts as a buffer for temporarily storing the detected positions. The clocking of the position FIFO block 38 is controlled by the control block 32 (as indicated at 40).

25 The detected position is fed from the position FIFO block 38 (as indicated at 42) to an in grid detector 44. The in grid detector 44 retrieves data from the grid description block 34 (as indicated at 46) and determines whether the received position is within the loaded grid description. If not, the in grid detector
30 44 notifies the control block 32, which in turn initiates a

request for a new grid. When the detected position is within the current grid, the position is then sent (as indicated at 50) from the in grid detector 44 to a stroke engine 52. The stroke engine 52 converts the received positions into strokes, which are then sent (as indicated at 54) to an action engine 56. A complete stroke is created when the electronic pen 10 is lifted from the paper or when it moves outside of the grid field where the stroke began. Finally, the action engine 56 converts the received stroke into an action that can be sent to the electronic pen client 22. By using grid action-field-types, the action engine knows which type of action to produce for a specific grid field.

Referring now to FIGURE 8, there is illustrated a block diagram of a state machine for the control block 32 shown in FIGURE 7. In this figure, events are indicated in capital letters, while tasks associated with the event are depicted in brackets. The process starts at step 60 with a start up event 62, which causes the position FIFO block 38 to begin receiving detected positions. Initially, the electronic pen 10 is in a no grid loaded state 64, which means that the electronic pen 10 does not have a grid loaded in the grid description block 34. As a result, the control block 32 generates an outside grid indication 66, thereby causing the electronic pen 10 to send the request for a new grid description to the electronic pen client 22 (i.e., in accordance with the new grid procedure) and to stop the FIFO buffer 38. At this point, the electronic pen 10 enters a waiting for grid state 68.

Once the new grid has been received (as indicated at 70), the control block 32 moves to a grid loaded state 72, at which time the new grid is loaded into the grid description block 34 and the position FIFO block 38 resumes operation. On the other hand,

if no grid is received (as indicated at 74), at least a portion of the positions stored in the FIFO buffer 38 are erased. Which part of the FIFO buffer to erase is determined by the grid exception area, if any, in the received empty grid description.

5 Accordingly, all positions stored in the FIFO buffer 38 that are within the grid exception area should be erased. If no grid exception is received, the stroke associated with the position is erased. In addition, the FIFO block 38 resumes operation and the control block 32 moves into the no grid loaded state 64.

10 When the control block 32 is in the grid loaded state 72, a current grid is loaded in the grid description block 34. While the control block 32 remains in this state 72, the position FIFO block 38 continues to receive detected positions and passes them on to the stroke engine 52 and action engine 56. Actions produced
15 by the action engine 56 are sent (as indicated at 58) to the electronic pen client 22 (i.e., in accordance with the action procedure described above).

At some point, an outside grid indication 74 may be received by the control block 32 from the in grid detector 44. The outside
20 grid event 74 causes the FIFO block 38 to stop generating new positions. In addition, the electronic pen 10 enters a flushing stroke and action state 76 wherein the strokes that are currently in the stroke engine 52 and the actions that are currently in the action engine 56 are flushed to the electronic pen client 22. Once
25 the stroke engine 52 and action engine 56 have been fully flushed (as indicated at 78), the electronic pen 10 sends a request for a new grid to the electronic pen client 22 and unloads the current grid. The control block 32 then moves back into the waiting for grid state 68.

As a general matter, the electronic pen 10 may be capable of supporting various different types of output, including audio, such as warning tones; visual, such as a flashing light; tactile, such as vibration; and/or ink. In some cases, it might be desirable to allow the user of the electronic pen 10 to turn off the ink of the pen 10, such as when the electronic pen is being used on a portion of the address pattern that is public or shared or when the user wants to be able to reuse the current sheet of paper.

The electronic pen client 22 will now be described in greater detail. Generally, the electronic pen client 22 is analogous to a regular web browser. It is responsible for loading applications from application servers 30 and for handling input from the electronic pen 10. Preferably, the electronic pen client 22 is located in a separate device from the electronic pen 10 itself. This is because it is desirable to minimize the size and power supply requirements of the electronic pen 10, which will likely be adversely affected by the processing resources and memory necessary to support the functions of the electronic pen client 22.

Referring now to FIGURE 9, there is illustrated a block diagram of a state machine for the electronic pen client 22. Initially, the electronic pen client 22 is in a no application loaded state 80. The electronic pen client 22 recognizes only one signal when in this state 80, namely a new grid request from the electronic pen 10. Such a request causes a load grid indication event 82. The electronic pen client 22 responds by sending a request to the name server 26 to translate a position contained within the new grid request into a URL where the application description can be found (i.e., in accordance with the find

application location procedure). Next, the electronic pen client 22 enters a waiting for application description URL state 84. If no URL for the application description can be found (as indicated at 86), the electronic pen client 22 sends a new grid reply to the electronic pen 10, wherein the reply contains an empty grid description with a grid exception. As a result, the electronic pen client 22 returns to the no application loaded state 80.

If a URL for the application description is received from the name server 26 (as indicated at 88), the electronic pen client 22 sends a request to the application server 30 to retrieve the application description (i.e., in accordance with the get application description procedure). Accordingly, the electronic pen client 22 enters a waiting for application description state 90.

If the electronic pen client 22 does not receive an application description from the application server 30 (as indicated at 92), a new grid reply is sent by the electronic pen client 22 to the electronic pen 10 wherein the reply contains an empty grid. Thus, the electronic pen client 22 returns to the no application loaded state 80. If, however, the electronic pen client 22 does receive an application description from the application server 30 (as indicated at 94), the electronic pen client 22 sends a new grid reply to the electronic pen 10 containing a new grid description, and the electronic pen client 22 loads the application in its memory. In addition, the electronic pen client 22 moves into an application loaded state 96.

In the application loaded state 96, five types of actions can be received by the electronic pen client 22 from the electronic pen 10. First, a received action can include a request

that the electronic pen client 22 cannot handle itself, in which case the electronic pen client 22 will send the action to the base translator 28 (as indicated at 98). The electronic pen client 22 then moves into a waiting for response from the base translator state 100. Once a base translator response 102 is received by the electronic pen client 22, the electronic pen client 22 updates a current form or other data associated with the currently loaded application and sends an action reply to the electronic pen 10 with appropriate output information.

Another type of action that the electronic pen client 22 can receive from the electronic pen 10 is a request that should be forwarded to a control node 24. In such a case, the action is sent to a control URL specified in the application description (as indicated at 104), and the electronic pen client 22 enters a waiting for response from the control state 106. Once a response is received from the control (as indicated at 108), the electronic pen client 22 sends an action reply to the electronic pen 10 with appropriate output information.

A third type of action is a submit form request, in response to which the electronic pen client 22 will submit the current form to the application server 30 that is identified by the URL in the application description (as indicated at 110). The electronic pen client 22 then enters a waiting for response from the application server state 112. If the application server 30 responds by sending an empty application description to the electronic pen client 22 (as indicated at 114), the current application is unloaded from the electronic pen client 22 and an action reply is sent to the electronic pen 10 with an empty grid. As a result, the electronic pen client 22 returns to the no application loaded state 80. On the other hand, if the application server 30

responds with a non-empty application description, the old application is unloaded from the electronic pen client 22, the new application description is parsed and loaded in the electronic pen client 22, an action reply is sent to the electronic pen 10 with
5 a new grid description and with appropriate output information, and finally the electronic pen client 22 returns to the application loaded state 96.

A fourth type of action that can be received by the electronic pen client 22 from the electronic pen 10 is a request
10 to load a new grid. This action occurs, for example, when a position outside of the current grid is detected by the electronic pen 10. When a new grid request is received, the electronic pen client 22 sends a request to the name server 26 (as indicated at 116) and the electronic pen client 22 returns to the waiting for
15 application description URL state 84.

Finally, a fifth type of action that can be received by the electronic pen client 22 is an action that the electronic pen client 22 can handle itself, in which case the electronic pen client 22 updates the current form and sends an action reply to
20 the electronic pen 10 with appropriate output information (as indicated at 118). The electronic pen client 22 then remains in the application loaded state 96. One type of action that the electronic pen client 22 might be able to handle itself is a local application. For example, the electronic pen client 22 might be
25 capable of performing certain basic functions that are defined by a local application. Thus, when the electronic pen client 22 receives a new grid request, the position associated with the new grid request can be analyzed to determine if it corresponds to a local application. If so, the electronic pen client 22 can load
30 the application description from its local memory, send a new grid

description to the electronic pen 10 without having to communicate with the name server 26 or the application server 30.

Another action that might be handled locally by the electronic pen client 22 relates to the selection of fields within a form. When the electronic pen client 22 receives an action, the field that corresponds to that action receives focus. When this occurs, the electronic pen client 22 might display the field's value on its display or output the value by audio. In addition, the electronic pen client 22 might allow the user to edit the value of the field by means other than the electronic pen 10. Yet another type of action that might be handled by the electronic pen client 22 itself are actions that relate to a clipboard function. When a "copy" field is selected, the value of the field that had focus at the time the copy field was selected is transferred to the clipboard. Similarly, when a "paste" field is selected, the value stored in the clipboard is transferred to the field that had focus at the time the paste field was selected.

Referring now to FIGURES 10A through 10C, there is shown, by way of example, a message flow and signaling diagram illustrating the operation of the electronic pen system 2 depicted in and discussed in connection with FIGURE 2. Initially, the electronic pen 10 detects a first position on the address pattern at step 120 (e.g., at a location on a sheet of paper designated for composing and sending emails). At this stage, it is assumed that the electronic pen 10 is in a no grid loaded state. Thus, in response to the detection of the first position, the electronic pen 10 sends a new grid request 122, which contains the detected position information, to the electronic pen client 22. As a result, the electronic pen client 22 sends an application location request 124 containing the detected position information to the name server

26, at step 126. The name server 26 translates the detected position into a URL where an application description that corresponds to the detected position can be found (e.g., a URL address for a server containing an email application), and returns
5 an application location reply 128 containing the retrieved URL to the electronic pen client 22.

The electronic pen client 22 then sends an application description request 130, which contains the unique pen ID for the electronic pen 10, to the application server 30. The application
10 server 30 retrieves the application description at step 132 and sends an application description reply 134 containing the retrieved application description to the electronic pen client 22. The electronic pen client 22 then parses and stores the application description at step 136. This step further involves
15 generating a current grid description from the application description and sending the grid description to the electronic pen 10 in a new grid reply 138. The electronic pen 10 stores the received grid description at step 140 and resumes processing of the detected positions. Using the detected positions and the
20 information in the grid description (e.g., so that the electronic pen 10 knows which fields of the email form are being filled in), the electronic pen 10 generates strokes at step 142 and generates actions at step 144 using the stroke engine 52 and action engine 56 shown in FIGURE 7.

Each time an action is generated that cannot be handled by the electronic pen 10 itself, an action request 146 containing a description of the action is sent from the electronic pen 10 to the electronic pen client 22. At this point, the electronic pen client 22 should determine what type of action has been received
25 so that it can respond to the action in an appropriate manner.
30

First, it is determined whether the action requires the attention of, or otherwise should be processed in accordance with, a local application at step 148. Very basic applications or frequently used applications (e.g., delete entered text), for example, might
5 be stored locally to avoid having to contact another entity. In such a case, the electronic pen client 22 retrieves the local application at step 150 and sends an action reply 152, which can contain a new grid description or other appropriate information.

However, if it is determined at step 148 that the received
10 action does not relate to a local application, the process continues at step 154 where it is determined whether the received action requires processing by an external translator (e.g., handwriting recognition). If so, an action request 156 containing a description of the action is sent by the electronic pen client
15 22 to the base translator 28. The base translator 28 processes the action at step 158 and sends an action reply 160 containing output information responsive to the received action (e.g., text corresponding to written characters) to the electronic pen client 22, which can forward the output information to the electronic pen
20 10 in an action reply 162, if necessary.

If it is determined at step 154 that the received action does not require processing by an external translator, it is next determined whether the action relates to a control application at step 164. If so, an action request 166 containing a description
25 of the action is sent by the electronic pen client 22 to the control server 24. The control server 24 processes the received action at step 168 and, if a response is necessary, returns output information responsive to the received action in an action reply 170, which is forwarded from the electronic pen client 22 to the
30 electronic pen 10 in an action reply 172.

Assuming that it is determined at step 164 that the received action does not relate to a control function, it is next determined whether the action comprises a request to submit a form at step 174 (e.g., a selection of a "send" area on the email form). If so, an action request 176 containing the data entered onto the form is sent by the electronic pen client 22 to the application server 30. The application server 30 processes the form at step 178 and sends an action reply 180 containing a new application description (or an empty application description) to the electronic pen client 22. The electronic pen client 22 parses and stores the new application description at step 182 and generates a new grid description from the newly received application description. The electronic pen client 22 then sends an action reply 184 containing the new grid description. Although not illustrated in the figure, the electronic pen 10 will typically respond to the receipt of a new grid description by unloading its current grid description and loading the new grid description into its memory.

At some point, it is assumed that the electronic pen 10 detects a position that is outside of the currently loaded grid at step 186. In response to such an event, the electronic pen 10 sends a new grid request 188 containing the newly detected position data to the electronic pen client 22. In response, the electronic pen client 22 again generates an application location request 190 containing the detected position data and sends the request to the name server 26. The name server 26 determines whether a URL for an application description that corresponds to the newly detected position is available at step 192.

If so, the name server 26 sends an application location reply 194 containing a retrieved URL to the electronic pen client

22, which in turn sends an application description request 196 containing the unique pen ID for the electronic pen 10 to the application server 30 at the identified URL address, just as previously discussed in connection with messages 128 and 130. In
5 this case, however, it is assumed that the application server 30 determines that the requested application description is unavailable at step 198. As a result, the application server 30 sends an application description reply to the electronic pen client 22 containing an empty application description. In
10 response to the receipt of an empty application description, the electronic pen client 22 unloads the current application at step 202 and sends a new grid reply 204 containing an empty grid description to the electronic pen 10. The electronic pen 10 responds to the receipt of the empty grid description by unloading
15 the current grid description at step 206.

Another possibility is that the name server 26 determines at step 192 that a URL corresponding to the detected position is not available. In this situation, the name server 26 sends an application location reply 208 to the electronic pen client 22.
20 The reply 208 may simply be empty to indicate that a URL is not available. Preferably, however, the reply 208 contains a grid exception defining the largest area possible around the detected position for which there is no corresponding URL. In response to the reply 208, the electronic pen client 22 sends a new grid reply
25 210 containing an empty grid description with a grid exception. Upon receiving the reply 210, the electronic pen 10 unloads the current grid description at step 212. Furthermore, assuming that the electronic pen 10 receives and recognizes the grid exception information, the electronic pen 10 may subsequently be able to
30 determine that certain detected positions on the address pattern

are not associated with any application without having to send a request to the name server 26 or the application server 30.

5 The electronic reading device system makes it possible to send a digital copy what is written on a piece of paper or a whiteboard, for example, as an email, fax, or SMS. This is simply performed by writing the message on the specially formatted intelligent paper. This technology can be combined with e-commerce technology stemming from the mobile terminal development. The combination results in an electronic pen that is well-suited
10 for e-commerce application.

The electronic pen 10 can also be used to perform electronic commerce. It requires, however, security algorithms, infrastructure solutions, and more to perform e-commerce in a secure and user-friendly manner with an electronic pen 10 (similar
15 to e-commerce solutions with a mobile terminal).

The solution to performing electronic commerce with an electronic pen 10 is to introduce an electronic commerce client into the electronic pen 10 that is the same as is integrated into mobile terminals (this would most likely be the Mobile electronic Transactions (MeT) client). The MeT client is a result of the MeT
20 Initiative, which is further described in the "MeT Overview White Paper" and other information available at www.mobiletransaction.org. Then, the electronic pen 10 can use the same infrastructure and standards as in mobile terminals, from a
25 system point of view, to perform e-commerce.

The user could then simply sign a note prepared according to this system 2 (i.e., on a paper that includes an address pattern) to accept a purchase and mark with the electronic pen 10 on the note which credit card to use (perhaps by circling the credit card
30 symbol). The purchase would then be done electronically with the

electronic pen 10, paper, signature, and credit card information stored at an electronic commerce server on the Internet. Thus, the user will accept and perform the purchase by signing the note in an ordinary fashion as is done today but with no physical credit cards involved. In addition, the information about the transaction is performed wirelessly with the electronic pen 10 connected to the Internet via either a mobile terminal or an access point. Furthermore, the electronic pen 10 could include intelligence such that the speed of writing, direction, and pressure of writing is known. This would enable a handwriting recognition algorithm stored in the server, electronic pen 10, or mobile phone 14 to safely verify a user's signature.

Referring now to FIGURES 1 and 2, an illustrative embodiment will now be described. To perform an electronic commerce transaction, a user would use an electronic pen 10 to select a type of credit card and sign a note printed on an addressed paper 12 associated with a particular vendor. The electronic pen 10 would detect what information is written and send the detected information to a base translator 28 via an electronic pen client 22 located in a mobile phone 14. A processor in the base translator 28 would then perform signature verification to authorize the transaction. The base translator 28 would also retrieve stored credit card information (e.g., credit card number, expiration date, billing address, etc.) associated with the selected type of credit card for the user. Alternatively, the credit card information could be stored in the electronic pen 10, electronic pen client 22, or at another server on the Internet. Moreover, retrieval of the credit card information and/or signature verification might be performed in response to a request from an application server 30 associated with the addressed paper

12. The retrieved credit card information would then be forwarded to an application server 30 associated with the address pattern on the paper 12 to complete the transaction. Verification of the completed transaction could then be electronically sent to the vendor.

Although various preferred embodiments of the method and apparatus of the present invention have been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it is understood that the invention is not limited to the embodiments disclosed, but is capable of numerous rearrangements, modifications, and substitutions without departing from the spirit of the invention as set forth and defined by the following claims. Furthermore, it shall be understood that the terms "comprises" and "comprising," when used in the foregoing Detailed Description and the following claims, specifies the presence of stated features, elements, steps, or components but does not preclude the presence or addition of one or more other features, elements, steps, components, or groups thereof.

WHAT IS CLAIMED IS:

1. An electronic reading device, comprising:
a sensor for detecting portions of an address pattern;
and

5 an electronic commerce client for communicating with a remote electronic commerce server to perform an electronic commerce transaction based on portions of the address pattern detected by the sensor.

10 2. The electronic reading device of claim 1, further comprising a wireless local link transmitter for transmitting information relating to the electronic commerce transaction to the electronic commerce server.

15 3. The electronic reading device of claim 2, wherein the information is transmitted to the electronic commerce server via a separate electronic device.

4. The electronic reading device of claim 1, wherein the electronic commerce client comprises an MeT client.

5. The electronic reading device of claim 1, further comprising a processor for performing user verification.

20 6. The electronic reading device of claim 5, wherein the processor performs user verification using a signature recognition functionality.

25 7. The electronic reading device of claim 6, wherein the signature recognition functionality comprises correlating a signature written using the electronic reading device with at least one of a detected speed of writing, a detected writing pressure, and a detected direction of writing.

8. The electronic reading device of claim 1, wherein the electronic commerce server comprises a credit card server.

9. A method of performing an electronic commerce transaction, comprising the steps of:

detecting portions of an address pattern using an electronic reading device;

5 converting the detected portions of the address pattern into electronic commerce transaction data; and

10 sending the electronic commerce transaction data to an electronic commerce server for performing an electronic commerce transaction in accordance with the electronic commerce transaction data.

10. The method of claim 9, wherein the electronic commerce server is compatible with MeT technology.

15 11. The method of claim 9, wherein the detected portions of the address pattern correspond to information written with the electronic reading device.



12. The method of claim 11, wherein the information written with the electronic reading device comprises a user signature.

13. The method of claim 12, further comprising the step of verifying the user signature.

20 14. The method of claim 13, wherein the step of verifying includes at least one of determining a speed of writing, determining a writing pressure, and determining a direction of writing.

25 15. The method of claim 9, wherein the step of sending comprises transmitting the electronic commerce transaction data via a wireless interface.

16. The method of claim 9, further comprising the step of notifying a vendor of an outcome of the electronic commerce transaction.






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 August 2001 (23.08.2001)

PCT

(10) International Publication Number
WO 01/61625 A3

(51) International Patent Classification⁷: **G06K 11/18.**
G06F 3/033

Magnus [SE/SE]: Filippavägen 6A, S-222 41 Lund (SE).
GÄRDENFORS, Torbjörn [SE/SE]: Kornettsgatan 24A,
S-211 50 Malmö (SE). JÖNSSON, Torsten [SE/SE];
Kornvägen 19, S-245 43 Staffanstorps (SE).

(21) International Application Number: PCT/EP01/01397.

(22) International Filing Date: 9 February 2001 (09.02.2001)

(74) Agent: **ERICSSON MOBILE PLATFORMS AB;**
SE-221 83 Lund (SE).

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/182,742	16 February 2000 (16.02.2000)	US
60/190,343	16 March 2000 (16.03.2000)	US
60/192,662	28 March 2000 (28.03.2000)	US
60/244,775	31 October 2000 (31.10.2000)	US
09/772,683	30 January 2001 (30.01.2001)	US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicant (*for all designated States except US*): **TELEFONAKTIEBOLAGET LM ERICSSON (publ)**
[SE/SE]: S-126 25 Stockholm (SE).


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **HÖLLSTRÖM,**

[Continued on next page]

(54) Title: **ELECTRONIC PEN FOR E-COMMERCE IMPLEMENTATIONS**



(57) Abstract: A method and apparatus for performing electronic commerce transactions uses an electronic reading device having a sensor that detects portions of an address pattern. An electronic commerce client communicates with a remote electronic commerce server to perform an electronic commerce transaction in accordance with portions of the address pattern detected by the sensor. For example, the detected portions of the address pattern can be converted by the electronic commerce client into electronic commerce transaction data and sent to the electronic commerce server.



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:

14 March 2002

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/01397

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G06K11/18 G06F3/033

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06K G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 905 248 A (RUSSELL GARRETT ET AL) 18 May 1999 (1999-05-18)	1-3, 9, 15, 16
Y	column 1, line 60 -column 3, line 26	5-8, 11-14
Y	WO 00 00928 A (LCI SMARTPEN NV) 6 January 2000 (2000-01-06) the whole document	5-8, 11-14
A	EP 0 717 367 A (SYMBIOS LOGIC INC) 19 June 1996 (1996-06-19) the whole document	6, 12-14
A	US 5 477 012 A (SEKENDUR ORAL F) 19 December 1995 (1995-12-19) the whole document	1, 9
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

18 October 2001

Date of mailing of the international search report

25/10/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Rydman, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/01397

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	<p>WO 01 48654 A (SKANTZE KRISTOFER ;WIEBE LINUS (SE); ANOTO AB (SE); ERICSON PETTER) 5 July 2001 (2001-07-05) page 3, line 1 -page 13, line 5 figure 1 -----</p>	<p>1-6, 9-13,15</p>

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 01/01397

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5905248	A	18-05-1999	US 6152369 A	28-11-2000
			US 5992752 A	30-11-1999
			US 6076733 A	20-06-2000
			US 5869819 A	09-02-1999
			US 5844227 A	01-12-1998
			US 6286760 B1	11-09-2001
			US 5808285 A	15-09-1998
			US 5557093 A	17-09-1996
			US 5525789 A	11-06-1996
			US 5661292 A	26-08-1997
			US 5484992 A	16-01-1996
			US 5591953 A	07-01-1997
			US 5616908 A	01-04-1997
			US 5874721 A	23-02-1999
			US 5260553 A	09-11-1993
			US 6068188 A	30-05-2000
			AU 5367998 A	22-06-1998
			AU 5513498 A	22-06-1998
			AU 7411698 A	22-06-1998
			BR 9713416 A	18-04-2000
			BR 9713425 A	25-01-2000
			BR 9713426 A	25-01-2000
			CN 1256772 A	14-06-2000
			CN 1246939 A	08-03-2000
			EP 0950226 A1	20-10-1999
			EP 0958546 A1	24-11-1999
			EP 1019844 A1	19-07-2000
			WO 9824049 A1	04-06-1998
			WO 9824036 A1	04-06-1998
			WO 9824050 A1	04-06-1998
			US 6227450 B1	08-05-2001
			US 6045048 A	04-04-2000
			US 6257492 B1	10-07-2001
			US 6027024 A	22-02-2000
			US 5905251 A	18-05-1999
			US 6283375 B1	04-09-2001
			US 6290132 B1	18-09-2001
			US 6182898 B1	06-02-2001
			US 6299067 B1	09-10-2001
			US 5767501 A	16-06-1998
			US 5942743 A	24-08-1999
			US 5796091 A	18-08-1998
			US 6073846 A	13-06-2000
			US 6085978 A	11-07-2000
			US 5984185 A	16-11-1999
			US 6112990 A	05-09-2000
			US 6003772 A	21-12-1999
			US 6199759 B1	13-03-2001
			US 6085980 A	11-07-2000
			US 5975419 A	02-11-1999
WO 0000928	A	06-01-2000	AU 4835299 A	17-01-2000
			CN 1312930 T	12-09-2001
			EP 1101188 A1	23-05-2001
			WO 0000928 A1	06-01-2000
EP 0717367	A	19-06-1996	DE 69522423 D1	04-10-2001
			EP 1130536 A2	05-09-2001

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 01/01397

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0717367	A	EP 0717367 A1	19-06-1996
		JP 8221189 A	30-08-1996
		US 2001000026 A1	15-03-2001
		US 6195446 B1	27-02-2001
US 5477012	A 19-12-1995	WO 9722959 A1	26-06-1997
		AU 4529896 A	14-07-1997
		US 5852434 A	22-12-1998
		EP 0892971 A1	27-01-1999
WO 0148654	A 05-07-2001	SE 0000946 A	24-06-2001
		WO 0148592 A1	05-07-2001
		WO 0148654 A1	05-07-2001
		SE 9904746 A	24-06-2001